

WENDEDÜSENTABELLE

Bohrung - Durchfluss - Spritzwinkel

Bohrung:		.018mm	.023mm	.028mm	.033mm	.038mm	.043mm	.048mm	.053mm	.058mm	.064mm	.069mm	.074mm	.078mm	.084mm	.089mm	.099mm	.109mm
		.007"	.009"	.011"	.013"	.015"	.017"	.019"	.021"	.023"	.025"	.027"	.029"	.031"	.033"	.035"	.039"	.043"
l/min:		0,2	0,3	0,5	0,7	0,9	1,1	1,5	1,7	2,1	2,5	2,9	3,3	4,1	4,5	4,9	6,2	7,8
Winkel	Spritzbreite*:																	
10°	5-10 cm	107	109	111	113	115	117											
20°	10-15 cm	207	209	211	213	215	217	219	221	223	225							
30°	15-20 cm	307	309	311	313	315	317	319	321	323	325			331		335		
40°	20-25 cm	407	409	411	413	415	417	419	421	423	425	427		431		435		443
50°	25-30 cm		509	511	513	515	517	519	521	523	525	527	529	531	533	535	539	543
60°	30-35 cm		609	611	613	615	617	619	621	623	625	627	629	631	633	635		
70°	35-40 cm					715	717	719	721	723	725			731		735		
80°	40-45 cm					815	817	819	821	823				831		835		
90°	45-50 cm							919	921									

* bei 30 cm Spritzabstand

Angaben dienen der Auswahl geeigneter Wendedüsen.

www.hausleitner-schweitzer.at

max. 500 bar